

D

DIVINE
FLOORING

Sound Solutions™

PE Foam 3 in 1

Underlayment For Laminate and Floating Wood Floors with Moisture Barrier

BENEFITS

- The moisture barrier film and tape strip combine to lock out moisture and allow for quick and easy installation
- Provides cushioned comfort under laminate and floating wood floors
- Eliminates minor subfloor imperfections
- Suitable for use with radiant heat flooring systems
- 100% recyclable, environmentally friendly
- Naturally resistant to mold and mildew
- Non allergenic and odorless

QUICK AND EASY INSTALLATION

Requires no additional seaming tape, cuts with a knife

1. Roll out underlayment with tape strip next to wall. Roll out next row in same manner butting underlayment close to first row (do not overlap) and covering the moisture

barrier film. Remove the tape strip and secure the overlapping moisture barrier film.

2. Install flooring according to the manufacturer's installation instructions

** NOT for glue down installations*

ROLL SIZES

4' x 25' (1.22 m x 7.62 m) – 100 sq. ft rolls

4' x 250' (1.22 m x 76.2) – 1000 sq. ft contractor size rolls

SOUND ABSORPTION PROPERTIES

Impact Insulation Class (IIC): This method is to measure the impact sound transmission performance of a floor-ceiling assembly (sound transmission through the floor)

IIC	Flooring	Sub-Floor
61	Laminate/Engineered Wood	6" concrete with ceiling assembly
54	Laminate/Engineered Wood	Wood joist with ceiling assembly

CANADA: 235075 Ryan Road SE, Rocky View, Alberta, Canada, T1X 0K3
Phone: 403-723-4100 **Fax:** 403-723-2338 **Email:** technical@divinefloor.com

USA: 900 N. Lake Shore Drive, Suite #2708, Chicago, IL 60611
Phone: 1-844-6 DIVINE (34 8463) **Fax:** 1-844-6 DIVINE (34 8463)

