

D

DIVINE
FLOORING

Sound Solutions™ SR

Engineered Wood & Laminate Flooring

Acoustical Underlayment with Moisture Barrier

Made of 100% synthetic rubber foam & suitable for all floating laminates, engineered and hardwood flooring.

BENEFITS

- Significantly reduces impact sound and floor to ceiling noise
- Adds firm cushion under laminates
- Non-allergenic and odorless
- Anti-microbial treatment, resists molds, mildew, and bacteria

SOUND RATINGS: IIC 72 and STC 74

ROLL SIZE: 3' x 33.34' (91.44 cm x 10.16 m)
100 sq. ft each

SIMPLE INSTALLATION

- Subfloor must be clean and dry before installation
- Install Divine Sound Solutions™ with film down against concrete/subfloor
- Roll out underlayment with tape strip side next to wall. Roll out next row in same manner butting foam close to first row (do not overlap) and covering the overlapping moisture barrier. Remove the tape strip and secure the overlapping moisture barrier. Install flooring per the manufacturer's instructions.

CANADA: 235075 Ryan Road SE, Rocky View, Alberta, Canada, T1X 0K3
Phone: 403-723-4100 **Fax:** 403-723-2338 **Email:** technical@divinefloor.com

USA: 900 N. Lake Shore Drive, Suite #2708, Chicago, IL 60611
Phone: 1-844-6 DIVINE (34 8463) **Fax:** 1-844-6 DIVINE (34 8463)

